PM2017B

AC Digital Clamp Meter

NEW

PATENTED



SPECIFICATIONS

	RANG	ACCURACY
DC Voltage	6V/60V/600V	± (0.5%+3)
	1000V	± (0.8%+3)
AC Voltage	6V/60V/600V	± (0.8%+5)
	1000V	± (1.0%+5)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ	± (1.0%+3)
	60MΩ	± (1.2%+30)
AC Current	6A	± (2.5%+8)
	60A/600A	± (2.5%+5)
Capacitance	60nF/600nF/6uF/60uF/ 600uF/6mF	± (4.0%+3)
	60mF	± (5.0%+5)
Frequency	10Hz/100Hz/1kHz/10kHz 100kHz/1MHz	± (1.0%+5)
K-type Thermocouple Temperature	-20°C~1000°C	± (2.0%+2)
	-4°F~1832°F	± (2.0%+2)

FEATURE

Display	6000 Counts
Backlight	√
Relative measurement	√
Manual /Automatic Range	√
Maximum/minimum measurement	√
Diode test	√
Continuity	√
Single probe live wire detection	√
NCV	√
Auto Power off	About 15 minutes
Low Battery Indication	√
Data Hold	√
VDF	√
True RMS	√

GENERAL

Power Supply	2×1.5V AAA batteries
Weight	Approx 189g (not include batteries)
Product Size	195×66×33mm
Maximum opening of clamp head	35mm
Safety Rating	IEC61010-1、IEC 61010-2-032 Shell CAT III 1000V Clamp shell CAT III 600V

DIGITAL CLAMP METERS

PM2018A

AC Digital Clamp Meter

PATENTED

SPECIFICATIONS

	RANGE	ACCURACY
DC Voltage	200mV/2V/20V/200V	±(0.8%+2)
	600V	±(1.0%+2)
AC Voltage	2V/20V	±(1.0%+5)
	200V/600V	±(1.2%+5)
AC Current	2A/20A	±(3.0%+15)
	200A/600A	±(3.0%+10)
Resistance	200Ω/2KΩ/20KΩ/200KΩ/2MΩ	±(1.2%+2)
	20MΩ	±(2.0%+5)

FEATURE

Display	2000 Counts
Range	Auto
Diode Test	√
Continuity	√
BackLight	√
NCV	√

GENERAL

Power Supply	2 x 1.5V AAA Batteries
Size	189mm×64mm×34mm
Jaw Size	Ø24mm
Safety Standard/Rating	EN61010-1,EN61010-2-032,EN61326,CAT.III 600V



DIGITAL CLAMP METERS