


T3001

Probe:Length 130mm,TipΦ2mm
Plug:Φ4mm Cross Plug,right angle type
Wire:20AWG,red/black
Length:1000mm
Safety Class:EN61010-031,1000V CATIII/600V CATIV,MAX 10A



T3002

Probe:Length 120mm,TipΦ2mm
Plug:Φ4mm Cross Plug,right angle type
Wire:22AWG,red/black
Length:800mm
Safety Class:EN61010-031,1000V CATII,MAX 10A



T3006

Probe:Length 130mm,TipΦ4mm Banana
Plug:Φ4mm Banana Plug,right angle type
Wire:18AWG,red/black
Length:1200mm
Safety Class:EN61010-031,1000V CATIII/600V CATIV,MAX 10A



PM3203
Diode-triode socket
For:PM8237



P3408A/B

K Type Thermocouple
Range:-40~260°C(-40°F~500°F)
Length:1000mm
Type A:Plug Length 12mm,Type B:Plug Length 16mm



P3409A/B

K Type Thermocouple
Range:-50~600°C(-58°F~1112°F)
Length:1000mm
Type A:Plug Length 12mm,Type B:Plug Length 16mm



P3412

K Type Thermocouple
Range:40~260°C(-40°F~500°F)
Length:1000mm



A3102
Big Mouth Alligator Clip,MAX 36mm
Plug：Φ4mm Jack
Color：Red&Black



MS3200

Multi-function socket
Feature: Transister Temperature
Capacitor
For: MY60/61/64/65



MS3201

Multi-Function Socket
Feature: Transister Temperature
Capacitor Inductance
For: MS81/85/86/88/89



B3801A/B

Size:
A:300X200X60mm
B:210X130X50mm
Material:Sacking
Colour:Black



B3802A/B

Size:
A:215X100X35mm
B:165X90X55mm
Material:Sacking
Colour:Black



F3901

FF250mA/250V,Φ5x20,VDE/UL



F3902

FF10A/250V,Φ5x20,VDE/UL



F3903



F3904

ACCESSORIES